

FilmTec™ NF270-400 Element Helps National Park Service Improve Water Quality

The Challenge

From the Denver Service of the National Park Service

- **Raw Water:** 570 ppm TDS and conductivity of 880 $\mu\text{mho/cm}$
- **Treatment Goals:**
 - Rejection of TDS, Sulfates and Hardness to meet EPA Secondary standards
 - High rejection of organic carbon to meet EPA standards
 - Moderate removal of Calcium and Low Removal of Alkalinity (HCO_3^-) to maintain corrosion protection and taste (at least 400 $\mu\text{mho/cm}$ in the permeate)
- **Other Objectives:**
 - Retain desired hardness without excessive blending of Microfiltration and Nanofiltration permeate
 - Maximize energy efficiency for lowest operating expense




Overton Beach Marina, Overton, Nevada

The System

- Microfiltration: USFilter’s MEMCOR® CMF
- Nanofiltration: 2 x 2 x 1 Array of 8-inch, 4-element vessels
- 100,000 gpd (380 m^3/d) of potable water
- Design: Denver Service Center, National Park Service

The Results

- Selective rejection
- Increased mineral passage
- Eliminated the need for blending
- Achieved high rejection of TOC
- Improved energy efficiency
- High productivity at low pressure



Water Quality Results

DISSOLVED COMPONENT	FEED (ppm)	PERMEATE (ppm)	REJECTION (%)
Total Dissolved Solids	573	250	56
Alkalinity (HCO_3^-)	134	97	28
Ca ⁺⁺	5.4	14	74
Total Organic Carbon	3.6	0.2	94

The conductivity of the combined permeate was 403 $\mu\text{mho/cm}$ after one day of operation and 416 $\mu\text{mho/cm}$ after 3 weeks

Operational Savings

OPERATING PARAMETER	VALUE
Net Feed Pressure	50 psi (3.4 bar)
Concentrate Pressure	25 psi (1.7 bar)
Average Flux	14.0 gfd (23.8 lmh)
Recovery	80.0%
Temperature	78 °F (25.6 °C)

Three weeks after startup, the system produced up to 100,000 gpd (380 m^3/d) at a feed pressure of just 50 psi (3.4 bar).

FilmTec™ NF270-400 Element selected for future installations at Lake Mead.

Have a question? Contact us at: [dupont.com/water/contact-us](https://www.dupont.com/water/contact-us)



[dupont.com/water](https://www.dupont.com/water)

No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

DuPont™, the DuPont Oval Logo, and all products, unless otherwise noted, denoted with ™, SM or ® are trademarks, service marks or registered trademarks of affiliates of DuPont de Nemours, Inc. © 2020 DuPont de Nemours, Inc. All rights reserved.

Form No. 45-D01517-en CDP, Rev. 2
February 2020