

FilmTec™ SW30XFR-400/34

Fouling Resistant Element



Be Bold Against Biofouling

Introducing: FilmTec™ SW30XFR-400/34 Fouling Resistant Element



Fouling-Resistant

Reduce CIP frequency



Durable


Maintain stable rejection despite multiple CIP



Low ΔP Element

Lower pressure drop
Improved hydraulic balance
Better cleanability

Biofouling Cycle – What if we could...



Reference

SW30XFR-400/34 and SW30XFR-400/34i are installed worldwide

Country	Capacity (m ³ /d)	Product	Installation Year
China	8,000	SW30XFR-400/34	2020
China	7,000	SW30XFR-400/34	2020
Cyprus	60,000	SW30XFR-400/34	2020
Indonesia	3,000	SW30XFR-400/34	2020
Singapore	8,000	SW30XFR-400/34	2020
UAE	33,000	SW30XFR-400/34i	2020
USA	9,000	SW30XFR-400/34	2020

Proven Performance



FilmTec™ SW30XFR-400/34

Less is More: Less Cleaning, More Uptime

Feature: Fouling-Resistant Design

Result: Reduce CIP Frequency by > 30%

Benefits: Reliable System, More Uptime, Stable System, Reduce RO Fouling, Reduce CIP



Side by side comparison made with seawater, UF pretreatment, 6 elements in series at Recovery 40%, and 13 LMH flux

SW30XFR-400/34 is a fouling-resistant SWRO element specifically designed to handle **biofouling** in SWRO Desalination Plants. This is achieved thanks to its **fouling-resistant** design, its **durable membrane chemistry** and its **low pressure drop** design.

Applications

1. SWRO Plants with biofouling challenge
2. Industrial utility water from seawater source
3. Municipal Desalination Plants
4. Upgrade of FilmTec™ SW30HRLE-400 and SW30HRLE-400i

Built to Last


Feature: Durable Membrane Chemistry

Result: Maintain stable rejection despite multiple CIP

Benefits: Stable water quality, Reliable System, More Uptime, Lower Total Cost of Ownership

Invest to Save tool:

- Calculate the benefits of higher durability: <https://www.DesalApp.com/>




Side by side comparison made with synthetic sea water, consisting of 7 CIP cycles of caustic (pH 12, 35°C) and acid (pH 2, 25°C) was performed side-by-side, followed by a stabilization standard test

When Low is High: Low ΔP, High Balance


Feature: Low ΔP Element

Result: Pressure drop reduced by 40%, Improved system hydraulic balance and better cleanability

Benefits: Reliable System, More Uptime, Reduce RO Fouling, Reduction in CIP



The hydraulic tests were performed registering the pressure drop evolution of the elements at increasing feed flow, ranging from 3 m³/h to 18 m³/h at a constant temperature of 25°C



Have a question? Contact us at: dupont.com/water/contact-us



dupont.com/water

No freedom from infringement of any patent or trademark owned by DuPont or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other government enactments. The product shown in this literature may not be available for sale and/or available in all geographies where DuPont is represented. The claims made may not have been approved for use in all countries. DuPont assumes no obligation or liability for the information in this document. References to "DuPont" or the "Company" mean the DuPont legal entity selling the products to Customer unless otherwise expressly noted. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted. © 2021 DuPont.